DATA SHEET



WBXRA160E DIGITAL VIDEO RECORDER

16 Channel 960H H.264 DVR without HDD

The WBXRA160E is a 16 channel Digital Video Recorder which can connect analogue cameras and provide powerful surveillance. This new generation DVR is widely applied in the areas of public security, education, communication, transportation, military, finance/ banking and various other installation applications.

- Max 0.375 MB Per Second @ 960H Resolution
- Real Time Recording
- Normal and Event Recording
- HDD Not Included
- Maximum Storage Capacity: 6 TB
- Supports Various Camera Resolutions
- Remote Live View By Mobile App
- Warranty 60 Months

LENGTH:	200mm
WIDTH:	200mm
HEIGHT:	45mm
WEIGHT:	1.2Kg



FOR MORE INFORMATION,

www.wboxtech.eu

Specifications

Model		WBXRA040E	WBXRA080E	WBXRA160E	
	Video compression	H.264			
Video/Audio input		4-ch	8-ch	16-ch	
	Analog video input	BNC interface (1.0Vp-p, 75 Ω), PAL / NTSC self-adaptive			
	Audio compression	G.711u			
	Audio input / Two- way audio in	1-ch, RCA (2.0 Vp-p, 1 KΩ)			
	HDMI / VGA output	1920 × 1080 / 60 Hz,1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz			
		Main stream: WD1 / 4CIF / VGA / CIF			
	Encoding resolution	Sub-stream:	Sub-stream: 4CIF (non-re	eal-time) / 2CIF (non-real-	
		2CIF (non-real-time) / CIF time) / CIF			
	Frame rate	1/16 fps ~ Real time frame rate			
Video/Audio	Video bitrate	32 Kbps ~ 4 Mbps			
output	Audio output	1-ch, RCA (Linear, 1KΩ)			
	Audio bitrate	64 Kbps			
	Dual-stream	Supported			
	Stream type	Video, Video & Audio			
	Synchronous playback	4-ch	8-ch	16-ch	
	Playback resolution	VGA / WD1 / 4CIF / CIF / QVGA / QCIF		F	
Network management	Remote connections	32	128	128	
	Network protocols	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS			
Hard disk	SATA	1 SATA interface			
	Capacity	Up to 6 TB capacity for each disk			
External	Network interface	1; 10M / 100M self-adaptive Ethernet interface			
interface	USB port	2 × USB2.0			
General	Power supply	12V dc			
	Consumption (without hard disks)	≤ 8W	≤ 12W	≤ 20W	
	Working temperature	-10 ºC ~+55 ºC (14 ºF ~ 131 ºF)			
	Working humidity	10% ~ 90%			
	Dimensions (W × D × H)	200 × 200 × 45mm (7.9 × 7.9 × 1.8 inch)		285 × 210 × 45 mm (11.2 × 8.3 × 1.8 inch)	
	Weight (without hard disks)	≤ 0.8 kg / 1.8 lb		≤ 1.2 kg / 2.6 lb	