



Features	Spider	Spider Duo
10/100 Ethernet	•	•
2nd Cascade Ethernet Port	•	
RS232 Port	•	•
USB Port (VIP Access bootstrap)		•
Remote Access (Up to 8 simultaneous connections)	•	•
Local Access		•
Video: HD15VGA	•	•
Compatible with DVI-A or DVI-I adapter	•	•
Keyboard/Mouse: USB	•	•
Keyboard/Mouse: PS2	•	•
Server Powered	•	
External Power Supply	Optional, 5VDC @ 1A	Included, 5VDC @ 2A
Cables Included	•	•
Standard Length Cables	21"	21.6"
Extended Length Cables	58"	59"
Resolution	1280x1024, 1024x768 800x600	1600x1200, 1280x1024, 1024x768, 800x600
IPv6 Ready		•
Browser Driven. Requires No Special Software Installation	•	•
Virtual Media	•	•
BIOS Level Access	•	•
Generate and Send Wake-On-LAN Packet	Firmware 3.0+	•
VIP Access	Firmware 2.2+	•
Power Control Unit Compatible		•
Telnet/SSH	•	•
HTTP/HTTPS	•	•
Local User/Group Authentication	•	•
Remote Authentication: LDAP, RADIUS, Active Directory	•	•
OS System Supported	Win 98/2000/2003/XP/Vista, Unix, Linux, MAC OSX 10	Win 2000/2003/2008/XP/Vista, Unix, Linux, MAC OSX 10
RoHS	•	•
Environmental Operating Temp	0° to 45° C (32° to 115° F)	0° to 45° C (32° to 115° F)
Environmental Storage Temp	-20° to 70° C (-4° to 158° F)	-20° to 70° C (-4° to 158° F)
Dimensions	13.2 x 5.8 x 3.1 cm (5.2 x 2.3 x 1.2 in)	13.2 x 5.8 x 3.6 cm (5.2 x 2.3 x 1.4 in)
Weight w/cables	185g (6.6 oz)	USB: 269g (9.50 oz) PS/2: 278g (9.80 oz)
Warranty	2 YR	2 YR