

SC-42



LED 

A quality and reliable 42" surveillance display featuring full HD resolution and wide viewing angles, is designed for security and control centre environments.

The SC-42 LED-backlit colour display, with Full HD resolution and 3000:1 contrast ratio, provides consistent colour and high digital image quality. The Anti-Burn-in™ technology prolongs the life time of TFT LCD panels. Quick signal-switching and built-in speakers maximise the effectiveness of real-time security monitoring. Versatile connectivity of analog and digital signals enables smooth system integration. Incorporated with looping BNC inputs, the SC-42 allows multiple display connections and is ideal choice for security and control environments.

- > FHD 1920 x 1080 resolution
- > Anti-Burn-in™ technology
- > Built-in Image Enhancer: 3D Comb Filter/Deinterlace/Noise Reduction
- > Versatile connectivity (VGA, HDMI, BNC in/out, S-Video, Audio in/out)
- > Looping BNC video inputs for multiple connections
- > Quick signal-switching time (<=0.8 sec.)
- > NTSC/PAL auto-detection
- > Selectable signal source
- > PC compatible
- > Built-in speakers
- > Auto-adjustment for optimal setting
- > Security socket
- > VESA standard wall mount



SC-42

Specifications

SC-42

Panel	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Viewing Angle (H/V) Display Colour Response Time	LED-Backlit TFT LCD (MVA panel) 42" FHD 1920 x 1080 0.485 mm 350 cd/m ² (Typical) 3,000:1 (Typical) 178°/178° 16.7M 3 ms (GTG)
Horizontal Resolution	TV Lines	625TVL (NTSC) 650TVL (PAL)
Frequency (H/V)		H: 31.5 kHz - 80 kHz V: 50 Hz - 75 Hz
Input	Analogue HDMI CVBS S-Video	15-Pin D-Sub HDMI BNC x 1 4-Pin mini DIN
Out	CVBS	BNC x 1
Audio	Audio In Audio Out Speaker	1 x stereo audio in for PC 1 x stereo audio out 2W x 2
Power	Power Supply Power Requirements Consumption	Internal 100 ~ 240V, 50 - 60Hz < 80 W (On)
Plug & Play	VESA	EDID
Operating Conditions	Temperature Humidity	0 °C ~ 40 °C 10% ~ 85%
Storage Conditions	Temperature Humidity	-10 °C ~ 50 °C 10% ~ 95%
Mounting	VESA FPMPI	Yes (400 x 400mm)
Dimensions	Product (W x H x D) Packaging (W x H x D)	992.3 x 656.3 x 240 mm (39.1" x 25.8" x 9.4") 1073 x 703 x 142 mm (42.2" x 27.7" x 5.6")
Weight	Product Weight Packaged Weight	14.5 kg (32 lbs) 16.5 kg (36.4 lbs)
Regulation Approval	Certifications & Compliance	CE, FCC, RoHS, WEEE
Accessories	Supplied	User manual, power cord, 15-Pin D-Sub cable, audio cable, warranty card



Stylish and slim design ideal for professional security environments



Built-in speakers enable more rigorous security monitoring



Looping BNC video inputs allow multiple display connections



Video versatility, including VGA, HDMI, S-Video and BNC In/Out