DATA SHEET



WBX DP TO HDMI

Product Code - WBXDPHDMI4

The newest built-in DP 1.2 chip can transfer high definition digital video and high quality audio signal to the display, projector or Monitor with HDMI Interface. HDMI output supports resolution upto 4K * 2K and 3D

- Support Display Port 1.1a/1.2 input, HDMI 1.3b/1.4b output and compatible with • Thunderbolt input port
- Support 3D HDMI supports audio output
- Compatible with HDTV, Display, Monitor, Projector and the other peripherals with HDMI . Interface
- Support HDMI 225MHz bandwidth, 2.25Gbps per channel (6.75Gbps all channel) and HDMI 12bit deep colour (36bit all channel deep colour)
- Can simultaneously connect multiple devices without any effect to the connection of other interfaces
- HDMI supports Ultra HD output and the maximum resolution of up to 4k * 2k (3840 * 2160 @ 30Hz)
- Applications: Macbook/ Macbook Air/ Mac Mini / IMac / MacPro etc
- Powered by Display port source
- Easy to Use, support plug & play with compact design.

The Display Port DP 1.2 to HDMI 1.4 Adapter Cable length: 23cm Operating temperature: 0 ° c to +70 ° c 400/ 1 05 6 RH

| Operating humidity: | 10% to 85% RH |
|----------------------|--------------------|
| Storage temperature: | -10 ° c to +80 ° c |
| Storage humidity: | 5% to 90% RH |
| Weight: | NW 26g /GW 39g |
| Warranty: | Limited Lifetime |
| | |



N FOR MORE INFORMATION, CONTACT YOUR ADI SALES PERSON.

www.wboxtech.eu