

FM-24




A 24" borderless and streamline design FHD display with superior dynamic contrast ratio 100,000,000:1 for home and office multimedia applications.

AG Neovo FM-24 LED backlight display features a 1.5mm bezel width slim and lightweight design. The Full HD 1920 x 1080 resolution, incredibly high dynamic contrast ratio and PLS panel enable FM-24 to present vivid images from all viewing angles. With the built-in speakers, dual PC and HDMI input connectors makes FM-24 the excellent multimedia display for home and working environments.

- > 24"wide screen LED-backlit display
- > Available in white and black
- > PLS panel provides consistent and accurate colour from all viewing angles
- > 1920 x 1080 Full HD resolution
- $>1.5~\mathrm{mm}$ borderless design for an invitingly modern appeal
- > Superior colour performance and colour contrast
- > HDMI input for Full HD connectivity with multi-media devices
- > Built-in speakers (2W x 2)
- > High intensity stand and base with skid proof design
- > Tilt capacity from -5°to 15°
- > Kensington® Security socket

FM-24

Specifications		FM-24
Panel	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Surface Treatments Viewing Angle (H/V) Display Colour Response Time	LED-Backlit TFT LCD (PLS Panel) 23.6" FHD 1920 x 1080 0.272 x 0.272 250cd/m² (Typical) 100,000,000:1 (DCR) Anti-glare treatment 178°/178° 16.7M 15ms (Typical)
Frequency (H/V)	H.Freq V.Freq	30kHz - 81kHz 56Hz - 75Hz
Input	VGA HDMI	15-Pin D-Sub HDMI
Audio	Audio In Speaker	1 x stereo audio in for PC (audio jack, 3.5 Ø) 2W x 2
Power	Power Supply Power Requirements Consumption	DC 19V/2A 100 – 240 V, 50-60 Hz < 30W (On) < 0.5W (Stand-by) < 0.5W (Off)
Operating Conditions	Temperature Humidity	5°C ~ 35°C (41°F ~ 95°F) 20% ~ 85%
Stand	Tilt Capacity	-5° ~ 15°
Dimensions	with Base (W x H x D) Packaging (W x H x D)	535 x 402 x 198 mm (21.1" x 15.8" x 7.8") 603 x 490 x 111 mm (23.7" x 19.3" x 4.4")
Weight	Product Weight (with base) Packaging Weight	3.1 kg (6.8 lbs) 4.6 kg (10.1 lbs)
Regulation Approval	Certifications & Compliance	CE, REACH, WEEE, ROHS
Accessories	Supplied	CD ROM (user manual), power cord, power adaptor, 15-Pin D-Sub cable, audio cable



1.5 mm borderless design for an invitingly modern appeal



Built-in HDMI input makes the FM-24 easy to be paired with Full HD multimedia devices



PLS panel provides superior clarity from all angles



User-friendly designed stand allows to tilt from -5° $\sim 15^{\circ}$



